


Features

- 1. Full beam, long Projection distance.
- 2. Light Source: PHILIPS 300s Flex, long life >6000hrs.
- 3. X / Y positioning is smooth and accurate.
- 4. Modular design for easy production, test and maintenance.
- 5. Colorful and changeable patterns.
- 6. Small size, light weight.
- 7. Professional thermal system design to ensure best heat dissipation.
- 8. 5 prisms, 11 prism effects.

Gobos & Colours

Static Gobo Wheel:



Color System:



Technical Parameters

Optical System

Light Source: Philips MSD Platinum 300S Flex

Optical Angle: 1.9°

Electrical Specification

Input Voltage: AC100~240V

Power: 550W

Power Connector: POWERCON Signal Connector: 3/5PIN XLR

Control System

Mechanical Movement: Pan 540°, tilt 270°(8~16bit scanning)

Dimming: Linear 0~100%, 4 dimming curve

Cooling System: Forced Convection

Control Protocol: DMX, RDM, W-DMX (wireless optional)

Channel Mode: 13CHS, 18CHS

Strobe: Mechanical strobe, Max. @14Hz random / pulsed

(optional)

Others: Self-rechargeable buffer battery, edit menu under no

power state, LCD screen

Working Environment

Working Temperature: 0°C~45°C

IP Rating: IP20

Dynamic Effects

Static Gobo Wheel: 18 gobos+open+animation effect

Color Wheel: 14 dichroic color filters+open, rainbow effect

with bi-directional and variable speeds

Prism: 2 groups×5 prims can get 11 prism effect. Bi-

directional rotating at variable speeds

Focus: Motorized linear focus

Frost: 0-100%

Physical Specification


Size: 374×355×628mm / 14.72"×13.97"×24.72"

N. W.: 21.5kg / 47.4lb

Housing: Flame-retardant plastic

Color: Black

Photometric Diagram



Size

